

Model # OBC6600-540V

1-Ph, 220/230/240V, 50/60Hz, 6.6KW 540V DC 12A Smart On Board Charger for E-Mobility Applications

Product Description

OBC6600-540V is a Magnizon's Smart 6.6KW, 540V/12Amp On board charger designed for pure E-mobility solutions. It adopts advanced resonant frequency modulation technology, high efficiency, large power, small size and reliable operation. The charging mode adopts constant power and constant voltage automatic state conversion, effectively reduces the charging time. With active power factor correction, zero pollution to the power grid, wide input and output voltage range, adopting CAN2.0B communication protocol, intelligent charging function, intelligent monitoring and fault alarm protection function, functions of remote detection, burning, fault inquiry, etc. Built in 12V independent auxiliary power supply for automotive BMS power supply. This power supply is designed for the charging of lithium ion batteries for new energy vehicles, and is fully synchronized with the world class automotive power suppliers. The performance indicators have reached or exceeded the international counterparts level, and the fault free operation time is longer upto 150,000hrs.



Liquid Cooled unit

Applications

- Lithium battery manufacturers
- Pure Electric vehicle manufacturing firms
- Cleaning cart, golf cart
- Logistics trucks, forklifts
- Sightseeing car, electric boat
- Battery energy storage equipment, UPS room equipment
- Customized special non-standard charger



Model # OBC6600-540V

Air Cooled unit

Key Features

Fully Sealed, Enforce air Cooling/Liquid Cooling (Module Optional)

- Reliable working under -35°C- +85°C
- Internal temperature sensor
- Shut off inside temperature over 90°C
- IP67 Protection Level
- Constant current and constant voltage automatic conversion, effectively save charging time
- Active power factor correction≥0.99
- Input over-voltage/under-voltage protection
- Output over-voltage/under-voltage protection
- Output over-current protection
- Output short circuit protection
- Output reverse connect protection
- Over-temperature protection
- CAN communication intelligent fault alarm, protection function
- Small volume, high power density
- Designed for new energy vehicles



Model # OBC6600-540V

Specifications

Magnizon Model:	OBC6600-540V
Capacity	6.6KW 540V 12A
	AC Nominal Input
Phases/ Lines	1-phase;Single Phase
Input Voltage /Current	95V - 265V AC /32A
Frequency	45Hz-60Hz
	DC Nominal Output
Output Mode	CC / CV
Output Power	6600W @ 220VAC ; 3300W@110VAC
Output Voltage	170V – 650V DC (Rated 540V)
Output Current	12A
CV Accuracy	±1%
CC Accuracy	±2%
Ripple Voltage Coefficient	0.05
Output Efficiency	>93% (Full loading)
	Low Voltage Output
Output Mode	CV
Output Voltage	13.8V/27.6V
CV Accuracy	±1%
Nominal Current	5A
	5.5A±0.5A
Max Current	
	CC Accuracy ±2%
Ripple Voltage Coefficient	0.01
Can Campuniantian	Communication
Can Communication	Optional
Baud Rate	125Kbps、250Kbps、500Kbps
Terminal Resistance	NO
	Security Protection
	Input Over-voltage Protection; Input Under-voltage Protection; Output Over-
Multi Protection	voltage Protection; Output Under-voltage Protection; Output Over-current
	Protection; Over-temperature Protection; Short-circuit Protection; Battery
	Reverse Connect Protection; Ground Protection; CAN communication
	Protection; Power-off Protection
	Miscellaneous specs
Operating temperature	Miscellaneous specs -35°C~+85°C
Operating temperature Storage temperature	Miscellaneous specs -35°C~+85°C -45°C~+95°C
	Miscellaneous specs -35°C~+85°C
Storage temperature	Miscellaneous specs -35°C~+85°C -45°C~+95°C
Storage temperature Operating humidity (%RH) Storage humidity (%RH)	Miscellaneous specs -35°C~+85°C -45°C~+95°C 20-90(No condensation)
Storage temperature Operating humidity (%RH) Storage humidity (%RH) Vibration	Miscellaneous specs -35°C~+85°C -45°C~+95°C 20-90(No condensation) 10-95(No condensation)
Storage temperature Operating humidity (%RH) Storage humidity (%RH) Vibration Cooling mode	Miscellaneous specs -35°C~+85°C -45°C~+95°C 20-90(No condensation) 10-95(No condensation) QC/T413-2002(Other parts required)
Storage temperature Operating humidity (%RH) Storage humidity (%RH) Vibration Cooling mode Insulation resistance(MΩ)	Miscellaneous specs -35°C~+85°C -45°C~+95°C 20-90(No condensation) 10-95(No condensation) QC/T413-2002(Other parts required) Water-cooled
Storage temperature Operating humidity (%RH) Storage humidity (%RH) Vibration Cooling mode Insulation resistance(MΩ) IP Level	Miscellaneous specs -35°C~+85°C -45°C~+95°C 20-90(No condensation) 10-95(No condensation) QC/T413-2002(Other parts required) Water-cooled Input-output-shell>10 (25°C,70%RH)
Storage temperature Operating humidity (%RH) Storage humidity (%RH) Vibration Cooling mode Insulation resistance(MΩ) IP Level	Miscellaneous specs -35°C~+85°C -45°C~+95°C 20-90(No condensation) 10-95(No condensation) QC/T413-2002(Other parts required) Water-cooled Input-output-shell>10 (25°C,70%RH) IP67 150,000 hours
Storage temperature Operating humidity (%RH) Storage humidity (%RH) Vibration Cooling mode Insulation resistance(MΩ) IP Level MTBF	Miscellaneous specs -35°C~+85°C -45°C~+95°C 20-90(No condensation) 10-95(No condensation) QC/T413-2002(Other parts required) Water-cooled Input-output-shell>10 (25°C,70%RH) IP67

Copyright © 2021 MAGNIZON POWER SYSTEMS. All rights reserved. All trademarks are the sole property of their respective owners. MAGNIZON POWER SYSTEMS has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.